# TECHNICAL DATA SHEET | ALUMINIUM-FRAMED GLASS DOUBLE-LEAF DOOR | INFO@VERTI.CZ | WWW.VERTI.CZ

# DOOR



# ALUMINIUM-FRAMED GLASS DOUBLE-LEAF

Suitable doors create a favorable overall impression of the environment, warmly welcoming all visitors, serving as a security feature, and providing protection from outside disturbances. We offer over 20 different door types to fit into any interior and complement VERTI partitions.









Aluminium-framed glass double-leaf door with overlight

## TECHNICAL SPECIFICATIONS

Description and use Interior aluminium-framed glass door without flange

Frame thickness 45 mm

Door Filling Insulating double glazing th. 29 mm, ESG 4 mm – alluminium frame – ESG 5 mm /

single glazing VSG 33/2

Lock mechanical / electromechanical / el. opener / magnetic


Basic Door Leaf Dimension 1600 / 2100 mm

Surface Finish ELOX / RAL painted

Installation Method into VERTI system partition / into opening including frame
Additional Equipment acoustic drop seal / self-closing mechanism / blinds

rectangular rosette / fittings of the customer's choice / mechanical / automatic latch

### STANDARD DOOR ARRANGEMENT



## DOOR DESIGN OPTIONS

